



NEVASTANE 2+

DESCRIPTION

Aluminum complex soap grease suitable for food industry.



No MOAH (Mineral Oil Aromatic Hydrocarbons).

*The Nevastane range will not contribute to MOAH content in foods when used in accordance with FDA 21CFR178.3570 limitations.

SPECIFICATIONS

- NEVASTANE 2+ is formulated in accordance with US FDA Regulation 21 CFR, 178.3570.
- NEVASTANE 2+ is NSF H1 registered: No 123541 and ISO 21469 certified.
- ISO 6743-9 : L-XBFFB 1/2
- DIN 51 502 : KP2R-20

APPLICATIONS

- NEVASTANE 2+ is a white Aluminum complex grease that surpasses other food grade greases by combining good anti-wear properties with good adhesiveness. Its specially designed additives provide increased wear resistance.
- NEVASTANE 2+ is stable over a wide temperature range. It can be used in various applications in the food industry as well as in multiple industrial applications.

ADVANTAGES

- NEVASTANE 2+ extends the equipment life while reducing contamination problems as required by the Hazard Analysis and Critical Control Point System (HACCP).
- NEVASTANE 2+ has excellent water and oxidation resistance as well as a high level of protection against corrosion, which allows for extended re-greasing intervals.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com

RECOMMENDATIONS

- Store the product at temperatures between 0 and 40°C.
- Shelf life: 2 years from date of manufacture (unopened).
- Always avoid contamination of the grease by dust and/or dirt when applying

TYPICAL CHARACTERISTICS

TYPICAL CHARACTERISTICS	METHODS	UNITS	NEVASTANE 2+
Soap/thickener	-	-	Aluminum Complex
Color	Visual	-	White
Appearance	Visual	-	Smooth
NLGI grade	ASTM D 217	Grade	2
Operating temperature range	-	°C	from -20 to 180
Penetration at 25 °C	ASTM D 217	0.1 mm	265-295
Four ball wear	ASTM D 2266	mm	0.63
Copper corrosion	ASTM D 4048	-	1A
Water washout 79°C	ASTM D 1264	% wt	<5
Dropping point	IP 396	°C	> 240
Base oil nature	DIN 51805	°C (mbar)	Mineral white oil
Kinematic viscosity of the base oil at 40 °C	ISO 3104	mm ² /s	105

Above characteristics are mean values given as an information.

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded at ms-sds.totalenergies.com